

# Kodak PIXPRO

Digital Cameras

## WP1 SPORT CAMERA



### FEATURES:

This rugged, waterproof KODAK PIXPRO WP1 Sport Camera is the perfect companion to get wet. Shockproof, dustproof and just about life proof, the WP1 was built to take on the go and be used in, on and under the water. With a host of scene modes to help you capture the best shot as well as HD video, the WP1 is not going to miss a beat. KODAK PIXPRO Digital Cameras - Tell your story.

- 16 Megapixels
- 5m Waterproof
- 1.2m Shockproof
- Dustproof
- 2.7" LCD
- AA Batteries



Available Colors:



# Kodak

## PIXPRO WP1

### Sport Camera



#### SPECIFICATIONS

#### WP1

Effective Image Sensor Pixels	16.15 Megapixels
Total Image Sensor Pixels	16.44 Megapixels [1/2.3" CCD]
Lens	
Focal Length	5.53 mm
[ 35mm film equivalent ]	[31.5 mm]
F number	F2.85
Lens Construction	5P
Optical Zoom	FF
Focusing Range	Normal: 60 cm — ∞
Digital Zoom	2x Digital Zoom
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608 x 3456, 10MP: 3648 x 2736, 5MP: 2592 x 1944, 3MP: 2048 x 1536, 0.3MP: 640 x 480,
Movie	(3:2) 14MP: 4608 x 3072, (16:9) 12MP: 4608 x 2592, 2MP: 1920 x 1080
Image Compression	1280 x 720: 30fps / 15fp, 640 x 480: 30fps
DCF, DPOF (Ver 1.1) Support	Best, Fine, Normal
File Format	Yes
Still Image	Exif 2.3 (JPEG)
Movie	Movie Format: MOV [Image: Motion JPEG; Audio: G.711 (Monaural)]
Shooting Modes	Auto, M, Panorama, Portrait, Movie, SCN (ASCN, Landscape, Sport, Beach, Sunset, Fireworks, Night Landscape, Snow, Children, ID, Glass, Photo Frame, Panning Shot, Text, Fish Eye, Party, Indoor, Leaf, Museum, Night Portrait, Sketch)
Detection Features	Face, Smile, Blink
Waterproof	Up to 16 ft. / 5m
Shockproof	Up to 3.93 ft. / 1.2m
Dustproof	Equivalent to JIS/IEC (IP6X)
Red-eye Removal	Yes
HDR	Yes (Post-Processing)
Stitch Panorama	Up to 180° (Horizontal)
LCD Display	2.7 inch (230K Pixels)
ISO Sensitivity	Auto, ISO 80/100/200/400/800/1600
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE
Exposure Compensation	+/- 2EV in 1/3 Step Increments
Shutter Type	Mechanical Shutter and Electronic Shutter
Speed	1/2000 - 4 Seconds (Manual: 30 seconds)
Continuous Shooting	Yes
Playback Modes	Single, Index (9/16 Thumbnails), Slide Show, Zoom (Approx. x2 - x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Underwater
Flash	
Flash Method	Internal
Flash Modes	Auto, Red-Eye Reduction, Fill Flash, Force Off, Slow Synchro, Red-Eye Reduction + Slow Synchro
Shooting Range	(Wide) Approx. 0.3 m - 5.1 m (ISO800)
Recycling Time	6 seconds or less
Recording Media	Internal Memory: Approx. 8MB
	Micro SD/Micro SDHC Card (Up to 32GB Supported) [MMC Card Not Supported]
PictBridge, ExifPrint Support	Yes
Jacks	AV-OUT/USB 2.0 (Micro 5 pin USB)
Power	AA Alkaline Battery (x2), AA NiMH Battery (x2) (Not Included)
Shooting Capability (Battery Performance)	Approx. 190 Shots from AA Alkaline Battery (Based on CIPA Standards)
Operation Environment	Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 4.21 x 2.35 x 1.10 in / 107.1 x 59.8 x 28.0 mm (Based on CIPA Standards)
Weight	Approx. 4.6 oz. / 130g (Body Only)
Supplied Accessories	AA Alkaline Battery (x2), USB Cable, Wrist Strap, Quick Start Guide, Warranty Card, Service Card

## JK Imaging Ltd.

JK Imaging, Ltd.  
1411 W. 190th Street, Suite 550  
Gardena, CA 90248

To learn more about KODAK PIXPRO Digital Cameras:  
visit: [www.kodakpixpro.com](http://www.kodakpixpro.com)

